

Buccaneer Excavator

The Bomford Buccaneer Excavator is suitable for use with excavators from 7 to 30 tonnes.
There are 4 ranges available:

SDH Range - With swinging hammers and 360° movement suited to mulch brush up to 200mm diameter.

SDFH Range - As above but suited to mulch brush up to 300mm diameter.

HDH Range - with fixed hammers, with tungsten carbide teeth suited to mulch brush up to 200mm diameter.

HDFH Range - As above but suited to mulch brush up to 300mm diameter.

Key Features

- Working with oil pressure ranges of 200 to 260psi
- Working with oil flows between 80 to 205 L/min
- Weight options from 912kg up to 1,902kg



Want to know more about the Buccaneer Excavator?

Scan the QR code to the left with a smart phone or tablet and compatible app to instantly view the page.

Alternatively visit: http://www.bomford-turner.com/forestry/buccaneer-excayator/





Protection

Double rows of heavy chains and adjustable skids.



Fixed hammers

Options available. Suitable for managing wooded areas.



Heavy duty drive 7 belt drive system.

| SDH Range | SDH130 | SDH150 | SDH180 |
|--------------------|---------------------|---------------------|---------------------|
| Working width | 1300mm / 4′3″ | 1500mm / 4′11″ | 1800mm/5′10″ |
| Transport width | 1500mm / 4'11" | 1750mm/5′8″ | 2000mm/6'6" |
| Cutting Diameter | 200mm | 200mm | 200mm |
| Number of Hammers | 20 | 20 | 20 |
| Number of Belts | 7 | 7 | 7 |
| Hammer Type | Swing | Swing | Swing |
| Weight | 957kg / 2110lbs | 1013kg / 2233lbs | 1070kg / 2359lbs |
| Oil flow L/min | 80-120L / 21-32 USG | 80-120L / 21-32 USG | 80-120L / 21-32 USG |
| Oil pressure (Bar) | 200-260 | 200-260 | 200-260 |

| HDH140 | HDH180 | |
|--------|--------|---------------|
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | HDH140 | HDH140 HDH180 |

| SDFH Range | SDFH130 | SDFH150 | SDFH180 |
|--------------------|---------------------|---------------------|---------------------|
| Working width | 1300mm / 4'3" | 1500mm / 4′11″ | 1800mm/5′10″ |
| Transport width | 1500mm / 4'11" | 1750mm / 5'8" | 2000mm/6'6" |
| Cutting Diameter | 200mm | 200mm | 200mm |
| Number of Hammers | 22 | 26 | 30 |
| Number of Belts | 7 | 7 | 7 |
| Hammer Type | Fixed | Fixed | Fixed |
| Weight | 912kg / 2011lbs | 960kg / 2116lbs | 1018kg/2244lbs |
| Oil flow L/min | 80-120L / 21-32 USG | 80-120L / 21-32 USG | 80-120L / 21-32 USG |
| Oil pressure (Bar) | 200-260 | 200-260 | 200-260 |