HE KING NO HA ING.

The world's favourite telehandler is now available with a 360° rotating boom. Introducing the 555-210R and 555-260R with 21 and 26 metre reach respectively. Our new JCB rotating telehandlers are simple to operate and offer all-round productivity, versatility, efficiency and safety. With over 45 years of manufacturing heritage, building our Loadall telescopic handlers, supported by the best dealer network in the business, supreme reliability and peace of mind is assured.



ALL- O ND IMPLICI .

Our new rotating telehandlers have the same simple, well designed controls as our standard telehandlers, delivering a similar operator experience across machines.

ALL- O ND E A ILI .

Our machines combine the reach and lifting capability of a crane, the manoeuvrability of a telehandler and the access of a mobile work platform, for 3-in-1 versatility.

ALL- O ND AFE .

Our new rotating telehandlers are designed for complete safety, with best-in-class visibility and load management system to keep you safe and secure at all times.

ALL- O ND P OD C I I .

Whatever the application, our rotating telehandlers have been extensively tested and proven in real world conditions to give you maximum performance.

ALL- O ND EFFICIENC .

Using 85% of shared JCB components, plus proven manufacturing and assembly techniques, we provide the very highest levels of quality, reliability and efficiency.

DIMENSIONS

			555-210R	555-260R
A	Overall height	m	3.08	3.08
B	Overall length	m	6.92	8.09
C	Overall width	m	2.45	2.45
D	Ground clearance	m	0.35	0.35
	Max lift height	m	20.5	25.5
	Max reach	m	17.8	21.4
	Max lift capacity	kg	5500	5500
	Capacity at max height	kg	2500	2000
	Capacity at max reach	kg	850	300
	Overall weight	kg	17960	19400
	Front axle unladen weight (boom retracted and lowered)	kg	8260	8660
	Rear axle unladen weight (boom retracted and lowered)	kg	9700	10740
	Turning radius (over tyres)	m	4.29	4.29

ENGINE

Type		JCB Dieselmax Stage V
Displacement	litres	4.8
Gross power	kW (hp)	112 (150) @ 2200 rpm
Max torque	Nm	600 @1500 rpm
Cylinders		4 in line
Fuel		Diesel direct injection turbocharged
Fuel tank	litres	190
AdBlue tank	litres	26
Gradeability		40%
Batteries	volts	2 x 12
Cooling system		Water – intercooler

TRANSMISSION AND HYDRAULICS

Transmission model	Bosch Rexroth
Transmission type	Two-speed hydrostatic
Drive wheels	4-wheel drive
Steering mode	4-wheel steer – 3 steering modes

HYDRAULICS

Type		Variable displacement pump electronically controlled with variable displacement motor
Flow rate	l/min	160
Movement control		2 servo electric joysticks
Operating system pressure	bar	290
Tank capacity	l	160

PERFORMANCE

Rotation	Continuous 360° rotation of turret mounted on external slew ring with in cab manual slew lock
Max travel speed	40kph

AXLES

Type	Dana Spicer – with epicyclic reduction gear
Model	213
Oscillation	±8° oscillation with automatic hydraulic lock out on rear axle

BRAKES

Type	Power brakes hydraulically activated, oil-immersed multi-disc type on each axle
Rear axle	SAHR park brake

OUTRIGGERS

Type	4x telescopic outriggers with one touch auto deploy/level/retract

LOAD MANAGEMENT SYSTEM

Full crane style load management system
7" screen with rotary controller
Envelope limits
5 configurable speed profiles

CARRIAGE

Type	Q-Fit carriage
Attachment recognition	RFID

TYRES

Type	445 / 65 R22.5

STANDARD CONFORMITY

EN1459-2
EN15830
EN14401
EN280
ROPS/FOPS
Stage V
ISO10896-2

555-210R LIFT PERFORMANCE – FORKS, 360° WITH OUTRIGGERS DEPLOYED



555-210R LIFT PERFORMANCE – 5.5T WINCH, 360° WITH OUTRIGGERS DEPLOYED

555-210R LIFT PERFORMANCE – 1000KG SLEWING MAN PLATFORM WITH OUTRIGGERS DEPLOYED



555-260R LIFT PERFORMANCE – FORKS, 360° WITH OUTRIGGERS DEPLOYED



PPDPP6

555-260R LIFT PERFORMANCE – 5.5T WINCH, 360° WITH OUTRIGGERS DEPLOYED

555-260R LIFT PERFORMANCE – 2T-2 METER JIB WINCH, 360° WITH OUTRIGGERS DEPLOYEDKPPDPP6

Your nearest JCB dealer

JCB Sales Limited, Rocester, Staffordshire, United Kingdom ST14 5JP.
Tel: +44 (0)1889 590312 Email: salesinfo@jcb.com

29460 08/21 -GB I I